

Our Reference: NA250909

21/05/2025

Amandah Smith
C/- Michael Bell Architects
C3 / 372 – 428 Wattle Street
ULTIMO NSW 2007

Attention: Attention Mr Michael Bell

Dear Michael,

Level 8, 55 Market Street, Sydney NSW 2000

PO Box Q577 Queen Victoria Building NSW 1230

T 02 9438 5098

Re: 47 East Crescent Street, Lavender Bay, Proposed Alterations and Additions

Further to our engagement by yourself, the writer visited the above property on the 17th April 2025 to assess the structural engineering constraints for the proposed alterations and additions as shown on the pre-DA drawings prepared by Michael Bell Architects.

During our visit, we met with your Architect, Michelle Bull, a builder, Tony Viscomi and a Geotechnical engineer, Ben Sheppard, from JK Geotechnics. The site visit revealed sandstone in the sub floor space, subsequently classified as very low strength sandstone, refer to the Geotechnical report (37572Srpt by JK Geotechnics).

Part of the proposed works will comprise of the excavation and western extension of the existing basement to create a new casual living, bathroom and wine cellar which would open out to a new courtyard. The existing basement floor level will be lowered by approximately 950mm, whereupon low strength sandstone bedrock will be exposed. To achieve the desired basement, traditional mass brick or concrete underpinning of the existing party will be required in a hit and miss methodology, refer to Section A / SK01, attached.

To create the new external courtyard, a removal of the existing courtyard pavers and an excavation of approximately 3.5m deep will be required. Prior to any excavation, a permanent shoring wall will be required, such as a contiguous piled cantilevered wall immediately adjacent to the Waiwera Street boundary, refer to Section B / SK01. Underpinning of the existing Bay window, down to bedrock will also be required prior to excavation, refer to Section C / SK01.

Excavation will progress through sandy fill material before encountering sandstone at approx. 900mm below the existing courtyard pavers. Excavation into rock will continue, leaving a column of rock under the existing house walls that are to be extended down, Refer to Section C / SK01. The wall extension will be using traditional underpinning techniques in a hit and miss fashion.





The underpinning and excavation works will be complex and there are risks of movement, if the correct procedures and monitoring regimes by the Geotechnical and Structural Engineers are not followed. The work is typically tedious, slow and time-consuming and it is essential that it is completed by Project Managers and tradespersons who are familiar with this type of work.

ACOR Consultants and JK Geotechnics have recently successfully completed two similar projects at 11 Holbrook Avenue, Kirribilli and 12 Bertha Road, Cremorne.

We have attached some photographs showing typical underpinning techniques and supporting structures required.

We trust the above meet your requirements at present. Please contact the undersigned if you require any further clarification.

Yours faithfully,

ACOR CONSULTANTS PTY LTD

Christopher Rowse

Senior Principal Engineer - Structural





11 Holbrook Ave, Kirribilli



Photograph 2

11 Holbrook Ave, Kirribilli





11 Holbrook Ave, Kirribilli



Photograph 4

11 Holbrook Ave, Kirribilli





11 Holbrook Ave, Kirribilli





12 Bertha Road, Cremorne



Photograph 7

12 Bertha Road, Cremorne

